

Optimized heat pumps for heating AW-HT 0122 - 0302



High efficiency heat pump, air source for outdoor installation, high water temperature 38,0-102 kW

AW-HT represent the best solution for systems in which there is the need to produce high temperature hot water for both space heating and sanitary purposes. With this solution the space heating can be easily provided by using radiators, so without any major changes on the already existing distribution system available on site. The EVI technology compressor with additional steam injection in the compressing cycle assures a water temperature of 65°C and operating limits as low as -20°C. Neither probes nor connections pipes to wells are needed; the installation is simple, this is a suitable solution for all applications.

Controls

W3000SE

The W3000SE controller is the new device designed especially for heat pump applications with incorporated logic for high temperature hot water production. The keypad features function controls and a complete LCD display for viewing data and activating the unit, via a multilevel menu, with settable display language. The controller provides temperature control for the heating and cooling systems in the air-conditioned rooms, as well as for domestic hot water. These different temperatures are managed automatically based on the different conditions in which the system operates, with the possibility to assign specific levels of priority to domestic hot water production, depending on the needs of the application. Diagnostics include complete alarm management, with "blackbox" functions (via PC) and alarm log (display or PC) for best analysis of unit behaviour. For systems made up of multiple units, differentiated device management means just a certain portion of the capacity installed can be dedicated to domestic water production, in this way ensuring more efficient energy distribution and, at the same time, guaranteeing simultaneous water delivery to the different distribution systems. The built-in clock can be used to create an operating profile containing up to 4 typical days and 10 time bands, essential for efficient programming of energy production, and fundamental for managing the Legionella prevention cycles. Defrosts use proprietary self-adaptive logic involving monitoring of multiple operating and climate parameters. This reduces the number and duration of defrosts, consequently increasing overall energy efficiency. Supervision is available with different options, using proprietary devices or by integration into third party systems using ModBus, BACnet, BACnet-over-IP and Echelon LonWorks protocols. A dedicated wall-mounted keypad can be used for remote control of all the functions.



Version

CA-E	Premium efficiency version: Class A enhanced
LN-CA-E	Premium efficiency version, Class A enhanced, low-noise

Configurations

-	basic function
D	partial condensing heat recovery function

Features

PREMIUM 'CLASS A' EFFICIENCY

The full range is available with a premium efficiency rating, over the Class A. AW-HT/CA-E and AW-HT/LN-CA-E guaranty premium levels of efficiency and quietness, making this range the best solution for both residential and light commercial markets.

MAXIMUM RELIABILITY

AW(R)-HT offer maximum operating reliability, thanks to their two main features:

- two independent circuits for all sizes;
- system to prevent formation of ice on the coil, ensuring shorter and more efficient defrost cycles.

EXTENSIVE RANGE OF OPERATION

Production of high temperature hot water up to 65°C for space heating and sanitary purposes. The unit can operate as standard down to -20°C outdoor temperature.

RENEWABLE ENERGY FOR COMMERCIAL INSTALLATIONS

Best solution in centralised residential systems such as apartment buildings, where the cost of renovation needs to be limited by keeping the same distribution system with radiators, while offering a source of renewable energy.

MODULAR CONFIGURATION

Modular configuration with capacity extension up to 400kW for medium- and high-capacity installations. Ability of managing different thermal loads according to the requirements of both heating and the domestic hot water systems.



APPLICATION HYDRONIC TERMINAL

AW-HT / CA-E			0122	0152	0202	0262	0302
Power supply	V/ph/Hz		400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
HEATING ONLY (GROSS VALUE)							
Total heating capacity	(1) kW		38,0	51,3	68,8	84,9	102
Total power input	(1) kW		10,7	14,4	19,4	23,6	27,7
COP	(1)		3,55	3,56	3,55	3,60	3,68
EXCHANGERS							
HEAT EXCHANGER USER SIDE IN HEATING							
Water flow	(1) m ³ /h		6,60	8,91	12,0	14,8	17,7
Pressure drop	(1) kPa		10,2	12,9	14,6	18,3	22,9
COMPRESSORS							
Compressors nr.	N°		2	2	2	2	2
No. Circuits	N°		2	2	2	2	2
NOISE LEVEL							
Noise Power	(2) dB(A)		84	86	87	87	87
Noise Pressure	(3) dB(A)		67	69	70	69	69
SIZE AND WEIGHT							
A	(4) mm		1695	2195	2745	2745	2745
B	(4) mm		1120	1120	1120	1120	1120
H	(4) mm		1465	1465	1465	1665	1665
Operating weight	(4) kg		510	750	870	940	1030

Notes:

1 Plant (side) heat exchanger water (in/out) 40°C/45°C; Source (side) heat exchanger air (in) 7°C - 87% R.H.

2 Sound power on the basis of measurements made in compliance with ISO 9614.

3 Average sound pressure level at 1m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.

4 Unit in standard configuration/execution, without optional accessories

APPLICATION FLOOR HEATING

AW-HT / CA-E			0122	0152	0202	0262	0302
Power supply	V/ph/Hz		400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
HEATING ONLY (GROSS VALUE)							
Total heating capacity	(1) kW		37,6	50,6	67,9	83,7	101
Total power input	(1) kW		8,90	12,2	16,3	19,9	23,2
COP	(1)		4,22	4,15	4,17	4,21	4,34
EXCHANGERS							
HEAT EXCHANGER USER SIDE IN HEATING							
Water flow	(1) m ³ /h		6,51	8,76	11,8	14,5	17,4
Pressure drop	(1) kPa		9,97	12,4	14,1	17,7	22,2
COMPRESSORS							
Compressors nr.	N°		2	2	2	2	2
No. Circuits	N°		2	2	2	2	2
NOISE LEVEL							
Noise Power	(2) dB(A)		84	86	87	87	87
Noise Pressure	(3) dB(A)		67	69	70	69	69
SIZE AND WEIGHT							
A	(4) mm		1695	2195	2745	2745	2745
B	(4) mm		1120	1120	1120	1120	1120
H	(4) mm		1465	1465	1465	1665	1665
Operating weight	(4) kg		510	750	870	940	1030

Notes:

1 Plant (side) heat exchanger water (in/out) 30°C/35°C; Source (side) heat exchanger air (in) 7°C - 87% R.H.

2 Sound power on the basis of measurements made in compliance with ISO 9614.

3 Average sound pressure level at 1m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.

4 Unit in standard configuration/execution, without optional accessories

APPLICATION HYDRONIC TERMINAL

AW-HT / LN-CA-E			0122	0152	0202	0262	0302
Power supply	V/ph/Hz		400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
HEATING ONLY (GROSS VALUE)							
Total heating capacity	(1) kW		38,4	51,0	69,4	85,8	100
Total power input	(1) kW		10,7	14,3	19,4	23,7	27,6
COP	(1)		3,59	3,57	3,58	3,62	3,63
EXCHANGERS							
HEAT EXCHANGER USER SIDE IN HEATING							
Water flow	(1) m ³ /h		6,67	8,86	12,1	14,9	17,4
Pressure drop	(1) kPa		10,5	12,7	14,8	18,7	22,2
COMPRESSORS							
Compressors nr.	N°		2	2	2	2	2
No. Circuits	N°		2	2	2	2	2
NOISE LEVEL							
Noise Power	(2) dB(A)		80	82	83	83	84
Noise Pressure	(3) dB(A)		63	65	66	65	66
SIZE AND WEIGHT							
A	(4) mm		1695	2195	2745	2745	2745
B	(4) mm		1120	1120	1120	1120	1120
H	(4) mm		1465	1465	1465	1665	1665
Operating weight	(4) kg		530	760	910	980	1030

Notes:

1 Plant (side) heat exchanger water (in/out) 40°C/45°C; Source (side) heat exchanger air (in) 7°C - 87% R.H.

2 Sound power on the basis of measurements made in compliance with ISO 9614.

3 Average sound pressure level at 1m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.

4 Unit in standard configuration/execution, without optional accessories

APPLICATION FLOOR HEATING

AW-HT / LN-CA-E			0122	0152	0202	0262	0302
Power supply	V/ph/Hz		400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50	400/3+N/50
HEATING ONLY (GROSS VALUE)							
Total heating capacity	(1) kW		38,0	50,2	68,5	84,7	99,0
Total power input	(1) kW		8,90	12,1	16,3	20,0	23,0
COP	(1)		4,27	4,15	4,20	4,24	4,30
EXCHANGERS							
HEAT EXCHANGER USER SIDE IN HEATING							
Water flow	(1) m ³ /h		6,58	8,69	11,9	14,7	17,1
Pressure drop	(1) kPa		10,2	12,2	14,4	18,1	21,5
COMPRESSORS							
Compressors nr.	N°		2	2	2	2	2
No. Circuits	N°		2	2	2	2	2
NOISE LEVEL							
Noise Power	(2) dB(A)		80	82	83	83	84
Noise Pressure	(3) dB(A)		63	65	66	65	66
SIZE AND WEIGHT							
A	(4) mm		1695	2195	2745	2745	2745
B	(4) mm		1120	1120	1120	1120	1120
H	(4) mm		1465	1465	1465	1665	1665
Operating weight	(4) kg		530	760	910	980	1030

Notes:

1 Plant (side) heat exchanger water (in/out) 30°C/35°C; Source (side) heat exchanger air (in) 7°C - 87% R.H.

2 Sound power on the basis of measurements made in compliance with ISO 9614.

3 Average sound pressure level at 1m distance, unit in a free field on a reflective surface; non-binding value calculated from the sound power level.

4 Unit in standard configuration/execution, without optional accessories

